

MODEL 2500UM UNIVERSAL MILLING MACHINE

SPECIFICATION :

TECHNICAL SPECIFICATIONS	MODEL 2500UM
TABLE	
Table area	1500x350mm (59x13.7")
Number of "T" shaped slots	5-16H7
Distance between "T" shaped slots	60mm
Rotary movement of table in both direction	45°
TRAVERSE	
Automatic Longitudinal	1150mm (46")
Automatic cross	400mm(15 3/4")
Automatic Vertical	500mm (20")
Available distance from spindle to overarm	155mm (6")
SPINDLE (horizontal)	
Housing of the taper spindle	ISO-40/50
Diameter of the main Shaft nose	88.88-128.57mm
Milling arbor diameter (*)	27mm or.(1")
Number of speeds of the spindle (R.P.M.)	12(40-1800) 50HZ
FEEDS	
Longitudinal and cross feeds	10-1208mm(0.4-47")
Vertical feed	5-604mm (0.2-23")

TECHNICAL SPECIFICATIONS	MODEL 2500UM
RAPID TRAVERSE	
Longitudinal and cross	1208mm(47")/min (60HZ)
Vertical	604mm(23")/min
PUISSANCE	
V-Belts	4
Main motor HP	7.5
Feed motor HP	2.5
COOLING	
Cooling-pump HP	1/8 (0.10)
MOTORIZED OVERARM	
Housing of the taper spindle	ISO-40/50
Number of speeds	12
Speed range (R.P.M.)	(35-1600) 50HZ
Power HP	5.5
WEIGHT	
Maximum weight on table	600kg (1320 lb)
Net weight	3200kg (7040 lb)
Gross weight with seapacking case	3400kg (7480 lb)
Cubical measure of packing	184x227x227cm (70x89x88")

STANDARD ACCESSORIES :

- ◆ 27mm or 1" long horizontal ISO#40 milling arbor.
- ◆ Horizontal & vertical manual draw-bars.
- ◆ Coolant pump & coolant system.
- ◆ Tool box and services tools.

OPTIONAL ACCESSORIES :

- ◆ AC auto for over - arm moving device is available.
- ◆ Ball screws for "X", "Y" axis.
- ◆ Auto ways lubrication unit.
- ◆ Chip tray.
- ◆ Universal dividing head, complete with 3 JAW chuck.
- ◆ Horizontal & vertical rotary table.
- ◆ Hydraulic clamping vise 6" or 8".
- ◆ Power milling vise 6" or 8".
- ◆ Clamping kit.
- ◆ Pneumatic power draw bar.
- ◆ ISO#50 spindle taper.